

## KODAK DRYVIEW™ 8700 Laser Imager

### Remarkable speed and image quality

Radiologists and other health imaging professionals prefer the Kodak DryView™ 8700 laser imager. It is by far the best-selling laser imager in the world, and it consistently earns nearly perfect ratings in independent studies of customer satisfaction. Now in its fourth generation, the Kodak DryView 8700 continues to deliver the exceptional speed and diagnostic image quality that radiologists demand. Plus, the DryView 8700 is a true dry *laser* imager. The laser diode never touches the film, and it never wears out—so you can count on steadfast reliability and consistency. The DryView 8700 is ideal for CT, MRI, DSA, and other high-volume 14 x 17-in. applications.

#### Unprecedented speed and image quality

- Up to 120 films per hour for maximum productivity
- 78-micron laser spot spacing, 325-dpi resolution
- Continuous-tone images with up to 4,096 gray levels
- Consistent resolution from application to application
- 1:1, 2:1, 4:1, 6:1, 9:1, 12:1, 15:1, 16:1, 20:1 formats
- Accommodates 20:1 format without compression

#### Proven reliability

- Flagship of the industry's most comprehensive family of true dry laser imagers
- Largest installed base of dry laser imagers—more than 15,000 systems placed worldwide
- Six years of clinical success
- Estimated 25,000 radiologists worldwide rely on DryView systems every day
- More than 350 million films produced to date

#### PACS Link connectivity

- PACS Link interface allows your facility to establish basic network printing *and* take an affordable first step toward PACS
- Converts image data from legacy modalities to DICOM, and receives DICOM image data over a network
- Sends image data over a network for softcopy viewing and archiving



**High-Volume  
14 x 17-in. Imaging**

#### Patented Automatic Image Quality Control

- Automatically calibrates the DryView 8700 to optimize image quality
- Requires no operator intervention, enhancing productivity
- Ensures contrast and density meet preset user preferences
- DryView film is system-matched for AIQC—so imagers recognize film type, size, lot, and number of sheets remaining

#### High-quality, system-matched film

- High-quality, silver-based film designed exclusively for Kodak DryView laser imagers
- Laboratory tested to deliver 100+ years of archivability
- Clear alphanumeric, optimum contrast, crisp edge sharpness
- Easy-to-load, recyclable film cartridge
- 125-sheet daylight-load cartridges
- Available in blue or clear, 7-mil polyester base

HEALTH IMAGING  
A BETTER VIEW OF LIFE.



# KODAK DRYVIEW™ 8700 Laser Imager

## SPECIFICATIONS

### Description

Kodak DryView 8700 laser imager

### Technology

Kodak DryView laser imaging

### DRYVIEW Image Quality

True dry laser technology  
78-micron laser spot spacing  
325-dpi laser resolution  
4,096 laser gray level reproduction

### DRYVIEW Laser Imaging Film

Lifetime film archivability  
(100+ years)  
14 x 17 in. (35 x 43 cm)  
Blue or clear base  
Instant daylight-load film  
cartridges  
125 sheets/cartridge

### KODAK Automatic Image Quality Control (AIQC)

Verifies printed density of each film  
Fully automatic—no user  
interaction or manual procedures  
necessary

### Throughput

Up to 120 films per hour

### PACS Link configuration

DICOM print service  
class provider  
Enables connectivity to a wide  
variety of DICOM modalities  
Converts image data from legacy  
modalities to DICOM

### Modality connections

Direct connect  
Network connect

### Dimensions

Height: 52 in. (132 cm)  
Width: 25 in. (63.5 cm)  
Depth: 32 in. (81 cm)  
Weight: 550 lb (250 kg)

### Electrical requirements

Voltage: 200/220/240 Hz ± 10%  
Frequency: 50/60 Hz ± 3 Hz

### Power consumption

700 VA (typical)

### Keypads

DryView keypad: 60 meters via  
copper connection  
Optional footswitch

### Operating environment

Temperature: 59° to 95° F  
(15° to 35° C)  
Humidity: 15% to 85% RH  
Magnetic field: 50 Gs (max.)

### Environmental effects

Heat load: 2300 BTU/hr (typical)  
Floor load: 125 lb/ft<sup>2</sup> (611 kg/m<sup>2</sup>)  
Acoustic noise: 55 dB normal  
operation (70 dB transient)

### Solutions for the way you work

Kodak's Health Imaging Division is committed to collaborating with you to find the right solutions to meet your radiological imaging and information needs now and in the future. Be sure to ask your Kodak representative for details on the compatibility of DryView laser imaging solutions with other products such as Kodak's Imaging Network Services, Kodak DirectView CR and DR systems, and PACS.



Health Imaging Division  
EASTMAN KODAK COMPANY  
343 State Street  
Rochester, NY 14650-1132  
USA  
Phone: 1-800-328-2910, option 3  
E-mail: info@kodak.com

KODAK CANADA INC.  
3500 Eglinton Avenue West  
Toronto, Ontario M6M 1V3  
CANADA

EASTMAN KODAK COMPANY  
305 Alexandra Road  
SINGAPORE 159942  
Fax: (65) 473-3861  
E-mail: medical@kodak.com

EASTMAN KODAK S.A.  
29-31 Route de l'Aéroport  
Case Postale CH-1212  
Geneve 15  
Switzerland  
Tel: +41 22 799 31 01  
Fax: +41 22 799 31 07

KODAK JAPAN LTD.  
Yamaman Building  
6-1, Koamicho, Nihonbashi, Chuo-ku  
TOKYO 103-8540  
JAPAN  
Tel: 03-5644-5160  
<http://www.kodak.co.jp/health>

EASTMAN KODAK COMPANY  
Latin America Region  
8600 NW 17th Street, Suite 200  
Miami, Florida 33126-1006  
USA  
Fax: 305-507-5055

[www.kodak.com/go/dryview](http://www.kodak.com/go/dryview)

